



# DuPont™ Multi-Use with Teflon® fluoropolymer Aerosol

## SAFETY DATA SHEET

OSHA HCS (29 CFR 1910.1200)

### SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

**Product identifier**

Chemical Name	Not applicable.
CAS No.	Mixture
Trade Name	DuPont™ Multi-Use with Teflon® fluoropolymer - Aerosol
Product Code	None

**Relevant identified uses of the substance or mixture and uses advised against**

Identified Use(s)	Lubricant
Uses Advised Against	None

Company Identification	Finish Line Technologies, Inc. 50 Wireless Blvd. Hauppauge, NY 11788
------------------------	--

Telephone	(631) 666-7300
E-Mail (competent person)	<a href="mailto:SDSinfo@finishlineusa.com">SDSinfo@finishlineusa.com</a>

**Emergency telephone number**

Emergency Phone No.	<b>Medical Emergency:</b> PROSAR 24 hr. 1-800-217-5157 / 1-651-523-0304
---------------------	---

**Transportation Emergency:** CHEMTREC 24 hr. 1-800-424-9300 / 1 (703) 527-3887 (Collect calls accepted)

### SECTION 2: HAZARDS IDENTIFICATION

**Classification of the substance or mixture**

OSHA HCS (29 CFR 1910.1200)	Flam. Aerosol 1; Skin Irrit. 2; Eye Irrit. 2; STOT SE 3; Asp. Tox. 1
-----------------------------	--

**Label elements**

Hazard Symbol



**DANGER**

Hazard Statement(s)

Extremely flammable aerosol.  
Pressurized container: May burst if heated.  
May be fatal if swallowed and enters airways.  
Causes skin irritation.  
May cause drowsiness or dizziness.

Precautionary Statement(s)

Keep away from heat/sparks/open flames/hot surfaces. – No smoking.  
Do not spray on an open flame or other ignition source.  
Pressurized container: Do not pierce or burn, even after use.  
Protect from sunlight and do not expose to temperatures exceeding 50 °C/122 °F.  
Avoid breathing spray.  
Wash hands and exposed skin thoroughly after handling:



# DuPont™ Multi-Use with Teflon® fluoropolymer Aerosol

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

Use only outdoors or in a well-ventilated area.

Keep out of reach of children.

None

Other hazards

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Ingredient(s)	% wt.	CAS No.
Heptane, branched, cyclic and linear	5 - 20	426260-76-6
Distillates (petroleum), hydrotreated light	40 - 60	64742-47-8
Distillates (petroleum), blend of various solvent-refined and hydrotreated heavy paraffinic and naphthenic	1 - 40	mixture
Propane	5 - 15	74-98-6
Butane	5 - 15	106-97-8
Proprietary Additives	<1	Trade Secret

Additional Information - None

## SECTION 4: FIRST AID MEASURES



### Description of first aid measures

Inhalation

Move person to fresh air. If breathing is labored, administer oxygen. If symptoms develop, obtain medical attention.

Skin Contact

Wash affected skin with soap and water. If symptoms develop, obtain medical attention.

Eye Contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If symptoms occur obtain medical attention.

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. Do not give anything by mouth to an unconscious person.

**Most important symptoms and effects, both acute and delayed**

May be fatal if swallowed and enters airways. Will cause skin irritation. Vapours may cause drowsiness and dizziness.

**Indication of any immediate medical attention and special treatment needed**

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

## SECTION 5: FIRE-FIGHTING MEASURES

### Extinguishing Media

-Suitable Extinguishing Media

Extinguish with carbon dioxide, dry chemical, foam or water spray.

-Unsuitable Extinguishing Media

Do not use water jet.



# DuPont™ Multi-Use with Teflon® fluoropolymer Aerosol

**Special hazards arising from the substance or mixture**

Highly flammable vapor (flash point below 23°C).

**Advice for fire-fighters**

A self contained breathing apparatus and suitable protective clothing should be worn in fire conditions. Keep containers cool by spraying with water if exposed to fire.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures**

Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Take precautionary measures against static discharges. Avoid contact with skin and eyes.

**Environmental precautions**

Prevent liquid entering sewers, basements and workpits.

**Methods and material for containment and cleaning up**

Cover spills with inert absorbent material. Transfer to a container for disposal or recovery.

**Reference to other sections  
Additional Information**

None  
None

## SECTION 7: HANDLING AND STORAGE

**Precautions for safe handling**

Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Avoid contact with skin and eyes. Use product in a well-ventilated area only.

**Conditions for safe storage, including any incompatibilities**

-Storage temperature

Keep in a cool, well ventilated place. Store at temperatures not exceeding 50°C / 122 °F.

-Incompatible materials

This product should be stored away from sources of strong heat or oxidising chemicals.

**Specific end use(s)**

Lubricant

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

**Occupational Exposure Limits**

SUBSTANCE.	CAS No.	(8hr TWA)		STEL		Note:
		PEL (OSHA)	TLV (ACGIH)	PEL (OSHA)	TLV (ACGIH)	
Heptane, branched, cyclic and linear	426260-76-6	500 ppm*	1500 mg/m <sup>3</sup>	-----	-----	*n-heptane
Oil mist (mineral)	-----	5 mg/m <sup>3</sup>	5 mg/m <sup>3</sup> <sup>(1)</sup>	-----	-----	<sup>(1)</sup> Inhalable
Propane	74-98-6	1000 ppm	Aspyx.#	-----	-----	#

\*Assure minimum oxygen content of work atmosphere.

**Recommended monitoring method**

NIOSH 1500 (hydrocarbons, B.P. 36 - 216 °C) ; NIOSH 5026 (Oil mist; mineral)

**Exposure controls**

**Appropriate engineering controls**

Provide adequate ventilation to ensure that the occupational exposure limit is not exceeded.

**Personal protection equipment**



# DuPont™ Multi-Use with Teflon® fluoropolymer Aerosol

Eye/face protection



Wear protective eyewear (goggles, face shield, or safety glasses).

Skin protection (Hand protection/ Other)



Wear suitable gloves if prolonged skin contact is likely (Nitrile rubber)

Respiratory protection



In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards

Not normally required.

**Environmental Exposure Controls**

None known

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

Appearance	Liquid / Liquefied gas
Color.	White (Translucent)
Odor	Petroleum spirit
Odor Threshold (ppm)	Not available
pH (Value)	Not available
Melting Point (°C) / Freezing Point (°C)	Not available
Boiling point/boiling range (°C):	Not available
Flash Point (°C)	-104 (Propane)
Evaporation Rate	Not available
Flammability (solid, gas)	Extremely flammable
Explosive Limit Ranges	2.1% - 9.5% v/v (Propane)
Vapour pressure (Pascal)	ca. 95 x 10 <sup>4</sup> (Propane)
Vapour Density (Air=1)	ca. 1.56 @ 0°C (Propane)
Density (g/ml)	Not available
Solubility (Water)	Not available
Solubility (Other)	Not available
Partition Coefficient (n-Octanol/water)	Not available
Auto Ignition Point (°C)	Not available
Decomposition Temperature (°C)	Not available
Kinematic Viscosity (cSt)	<10 @ 40 °C
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.

### Other information

VOC content = 25% by wt.

## SECTION 10: STABILITY AND REACTIVITY

<b>Reactivity</b>	Stable under normal conditions.
<b>Chemical stability</b>	Stable.
<b>Possibility of hazardous reactions</b>	None anticipated.
<b>Conditions to avoid</b>	Avoid contact with heat and ignition sources.
<b>Incompatible materials</b>	Strong oxidising agents



# DuPont™ Multi-Use with Teflon® fluoropolymer Aerosol

Hazardous decomposition product(s)

Carbon monoxide, Carbon dioxide, Acrid smoke, Other

## SECTION 11: TOXICOLOGICAL INFORMATION

Exposure routes: Inhalation, Skin Contact, Eye Contact

**Acute toxicity**

Oral: LD50 >5 g/kg-bw  
 Dermal: LD50 >2 g/kg-bw  
 Inhalation: LC50 = 65 - 103 mg/L (Vapor), 4-hr. rat  
 May cause drowsiness or dizziness.  
 May be fatal if swallowed and enters airways.

**Irritation/Corrosivity**

Causes skin irritation. Repeated exposure may cause skin dryness or cracking. Causes eye irritation.

**Sensitization**

It is not a skin sensitizer. Contains: N-Phenyl-1-naphthylamine (CAS# 90-30-2; <0.1%). May produce an allergic reaction in persons already sensitised.

**Repeated dose toxicity**

NOAEC: 12350 mg/m3 (2 yr, inhal., rat, Systemic effects)  
 LOAEC: 1650 mg/m3 (2 hr, inhal., rat, CNS effects)  
 May cause drowsiness or dizziness.

**Carcinogenicity**

No data. It is unlikely to present a carcinogenic hazard to man.

NTP	IARC	ACGIH	OSHA	NIOSH
No.	No.	No.	No.	No.

**Mutagenicity**

There is no evidence of mutagenic potential.

**Toxicity for reproduction**

No information available

## SECTION 12: ECOLOGICAL INFORMATION

Toxicity - Substances in preparations / mixtures

Heptane, branched, cyclic and linear (CAS# 426260-76-6) - By analogy with similar materials:

Short term

LL50 (96 hour): >13.4 mg/L (*Oncorhynchus mykiss*)  
 EL50 (48 hour): 3 mg/l (*Daphnia magna*, mobility)  
 EC50 (96 hour): 13 mg/l (*Pseudokirchnerella subcapitata*)

Long Term

NOELR (28 days) 1.5 mg/l (*Fish*) QSAR  
 LOEC (21 days): 0.32 mg/l (*Daphnia magna*)  
 NOEL (96 hour) 6.3 mg/l (*Algae*)

**Persistence and degradability**

Not available.

**Bioaccumulative potential**

Not available.

**Mobility in soil**

Not available.

**Results of PBT and vPvB assessment**

Not classified as PBT or vPvB.

**Other adverse effects**

None known.



# DuPont™ Multi-Use with Teflon® fluoropolymer Aerosol

## SECTION 13: DISPOSAL CONSIDERATIONS

**Waste treatment methods**

Disposal should be in accordance with local, state or national legislation. Consult an accredited waste disposal contractor or the local authority for advice.

## SECTION 14: TRANSPORT INFORMATION

	<u>Land transport (U.S. DOT)</u>	<u>Sea transport (IMDG)</u>	<u>Air transport (ICAO/IATA)</u>
UN number	1950	1950	1950
Proper Shipping Name	Aerosols, flammable	Aerosols, flammable	Aerosols, flammable
Transport hazard class(es)	2.1	2.1	2.1
Packing group	Not applicable	Not applicable	Not applicable
Environmental hazards	No.	No.	No.
Special precautions for user	None assigned	None assigned	None assigned

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: Not applicable

## SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture:

TSCA (Toxic Substance Control Act) - Inventory Status: All components listed or polymer exempt.

Designated Hazardous Substances and Reportable Quantities (40 CFR 302.4):

Chemical Name	CAS No.	Typical %wt.	RQ (Pounds)
None	----	----	----

SARA 311/312 - Hazard Categories:

Fire     Sudden Release     Reactivity     Immediate (acute)     Chronic (delayed)

SARA 313 - Toxic Chemicals (40 CFR 372):

Chemical Name	CAS No.	Typical %wt.
None	----	----

SARA 302 - Extremely Hazardous Substances(40 CFR 355):

Chemical Name	CAS No.	Typical %wt.	TPQ (pounds)
None	----	----	----

California Proposition 65 List:

Chemical Name	CAS No.	Type of Toxicity
None	----	----

## SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements: 1-16.

Date of preparation: July 14, 2014

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It



**DuPont™ Multi-Use  
with Teflon® fluoropolymer  
Aerosol**

may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.