



DuPont™ Non-Stick Dry Film Lubricant with Teflon® Fluoropolymer Liquid

SAFETY DATA SHEET

OSHA HCS (29 CFR 1910.1200)

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Chemical Name	Not applicable.
CAS No.	Mixture
Trade Name	DuPont™ Non-Stick Dry Film with Teflon® Fluoropolymer - Liquid
Product Code	None

Relevant identified uses of the substance or mixture and uses advised against

Identified Use(s)	Lubricant
Uses Advised Against	None

Company Identification	Finish Line Technologies, Inc. 50 Wireless Blvd. Hauppauge, NY 11788
------------------------	--

Telephone	(631) 666-7300
E-Mail (competent person)	SDSinfo@finishlineusa.com

Emergency telephone number

Emergency Phone No.	Medical Emergency: PROSAR 24 hr: 1-800-217-5157 / 1-651-523-0304
---------------------	---

Transportation Emergency: CHEMTREC 24 hr. 1-800-424-9300 / 1 (703) 527-3887 (Collect calls accepted)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the substance or mixture

OSHA HCS (29 CFR 1910.1200)	Flam. Liq. 2; Skin Irrit. 2; Eye Irrit. 2; STOT SE 3; Asp. Tox. 1
-----------------------------	---

Label elements

Hazard Symbol



DANGER

Signal Word(s)

Hazard Statement(s)

Highly flammable liquid and vapour.
May be fatal if swallowed and enters airways.
Causes serious eye irritation.
Causes skin irritation.
May cause drowsiness or dizziness.

Precautionary Statement(s)

Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Keep container tightly closed.
Wash hands and exposed skin after use.
IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

Other hazards

Keep out of reach of children.
None



DuPont™ Non-Stick Dry Film Lubricant with Teflon® Fluoropolymer Liquid

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Ingredient(s)	% wt.	CAS No.
Isopropanol	55 - 65	64-67-0
Heptane, branched, cyclic and linear	25 - 35	426260-76-6

Additional Information - None

SECTION 4: FIRST AID MEASURES



Description of first aid measures

Inhalation	Move person to fresh air. If breathing is labored, administer oxygen. If symptoms develop, obtain medical attention.
Skin Contact	Wash affected skin with soap and water. If irritation (redness, rash, blistering) develops, get medical attention. Take off contaminated clothing and wash it before reuse.
Eye Contact	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical advice/attention.
Ingestion	Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. Do not give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and delayed

May be fatal if swallowed and enters airways.

Indication of any immediate medical attention and special treatment needed

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

- Suitable Extinguishing Media: Extinguish with carbon dioxide, dry chemical, foam or water spray.
- Unsuitable Extinguishing Media: Do not use water jet.

Special hazards arising from the substance or mixture

Highly flammable vapor (flash point below 23°C).

Advice for fire-fighters

A self contained breathing apparatus and suitable protective clothing should be worn in fire conditions. Keep containers cool by spraying with water if exposed to fire.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Take precautionary measures against static discharges. Avoid contact with skin and eyes. Avoid breathing vapours.

Environmental precautions

Prevent liquid entering sewers, basements and workpits.



DuPont™ Non-Stick Dry Film Lubricant with Teflon® Fluoropolymer Liquid

Methods and material for containment and cleaning up Cover spills with inert absorbent material. Transfer to a container for disposal or recovery.

Reference to other sections None

Additional Information None

SECTION 7: HANDLING AND STORAGE

Precautions for safe handling Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Use explosion-proof electrical / ventilating / lighting / equipment. Avoid contact with skin and eyes. Use product in a well-ventilated area only. Avoid breathing vapours.

Conditions for safe storage, including any incompatibilities

-Storage temperature Keep out of reach of children. Keep in a cool, well ventilated place. Keep container tightly closed.

-Incompatible materials This product should be stored away from sources of strong heat or oxidising chemicals.

Specific end use(s) Lubricant

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

SUBSTANCE.	CAS No.	(8hr TWA)		(STEL)		Note:
		PEL (OSHA)	TLV (ACGIH)	PEL (OSHA)	TLV (ACGIH)	
Heptane, branched, cyclic and linear	426260-76-6	500 ppm*	1500 mg/m ³	-----	-----	*n-heptane
Isopropanol	67-63-0	400 ppm	200 ppm	-----	400 ppm	-----

Recommended monitoring method NIOSH 1500 (hydrocarbons, B.P. 36 - 216 °C); NIOSH 1400 (Alcohols I)

Exposure controls

Appropriate engineering controls Provide adequate ventilation to ensure that the occupational exposure limit is not exceeded.

Personal protection equipment

Eye/face protection



Wear protective eyewear (goggles, face shield, or safety glasses).

Skin protection (Hand protection/ Other)



Wear suitable gloves if prolonged skin contact is likely (Nitrile rubber). Check with protective equipment manufacturer's data.

Respiratory protection



In case of insufficient ventilation, wear suitable respiratory equipment. Check with protective equipment manufacturer's data.



DuPont™ Non-Stick Dry Film Lubricant with Teflon® Fluoropolymer Liquid

Thermal hazards

Not normally required.

Environmental Exposure Controls

Avoid release to the environment.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Liquid
Color.	White (Translucent)
Odor	Petroleum spirit
Odor Threshold (ppm)	Not available
pH (Value)	Not available
Melting Point (°C) / Freezing Point (°C)	Not available
Boiling point/boiling range (°C):	94 - 98 (201 - 208 °F)
Flash Point (°C)	-8 (18 °F)
Evaporation Rate	Not available
Flammability (solid, gas)	Not applicable
Explosive Limit Ranges	Not available
Vapour pressure (Pascal)	Not available
Vapour Density (Air=1)	Not available
Density (g/ml)	Not available
Solubility (Water)	Insoluble
Solubility (Other)	Not available
Partition Coefficient (n-Octanol/water)	Not available
Auto Ignition Point (°C)	Not available
Decomposition Temperature (°C)	Not available
Kinematic Viscosity (cSt)	<20 @ 40 °C
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
Other information	Not available

SECTION 10: STABILITY AND REACTIVITY

Reactivity	Stable under normal conditions.
Chemical stability	Stable.
Possibility of hazardous reactions	None anticipated.
Conditions to avoid	Avoid contact with heat and ignition sources.
Incompatible materials	Strong oxidising agents
Hazardous decomposition product(s)	Carbon monoxide, Carbon dioxide, Acrid smoke, Other

SECTION 11: TOXICOLOGICAL INFORMATION

Exposure routes: Inhalation, Skin Contact, Eye Contact

Toxicity - Substances in preparations / mixtures

Information on toxicological effects

Isopropanol (CAS# 67-63-0):

Acute toxicity

Oral: LD50 = 5.84 g/kg (rat)
Inhalation: LC50 > 1000 ppm (rat) 6 hour(s)
Dermal: LD50 = 16.4 ml/kg (rabbit) 24 hour(s)
May cause drowsiness or dizziness.

Irritation/Corrosivity

Irritating to eyes.



DuPont™ Non-Stick Dry Film Lubricant with Teflon® Fluoropolymer Liquid

Sensitization It is not a skin sensitizer.

Repeated dose toxicity NOAEL = 5,000 ppm (Inhalation)
May cause drowsiness or dizziness.

Carcinogenicity It is unlikely to present a carcinogenic hazard to man.

NTP	IARC	ACGIH	OSHA	NIOSH
No.	No.	No.	No.	No.

Mutagenicity There is no evidence of mutagenic potential.

Reproductive toxicity Not available

Heptane, branched, cyclic and linear (CAS# 426260-76-6) - By analogy with similar materials:

Acute toxicity Oral: LD50 >5 g/kg-bw
Dermal: LD50 >2 g/kg-bw
Inhalation: LC50 = 65 - 103 mg/L (Vapor), 4-hr. rat
May cause drowsiness or dizziness.
May be fatal if swallowed and enters airways.

Irritation/Corrosivity Causes skin irritation. Repeated exposure may cause skin dryness or cracking. May cause eye irritation.

Sensitization It is not a skin sensitizer.

Repeated dose toxicity NOAEC: 12350 mg/m3 (2 yr, inhal., rat, Systemic effects)
LOAEC: 1650 mg/m3 (2 hr, inhal., rat, CNS effects)
May cause drowsiness or dizziness.

Carcinogenicity No data. It is unlikely to present a carcinogenic hazard to man.

NTP	IARC	ACGIH	OSHA	NIOSH
No.	No.	No.	No.	No.

Mutagenicity There is no evidence of mutagenic potential.

Toxicity for reproduction No information available

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity

Isopropanol (CAS# 67-63-0):

Short term LC50 (96 hour): 10,000 mg/l (Fathead minnow (*Pimephales promelas*))
LC50 24hour(s): >10,000 mg/l (*Daphnia magna*)

Long Term NOEC: 3.37 µmol/l (*Daphnia magna*) (Growth rate)

Persistence and degradability Not available.

Bioaccumulative potential Not available.

Mobility in soil Not available.

Results of PBT and vPvB assessment Not classified as PBT or vPvB.

Other adverse effects None known.

Heptane, branched, cyclic and linear (CAS# 426260-76-6) - By analogy with similar materials:

Short term LL50 (96 hour): >13.4 mg/L (*Oncorhynchus mykiss*)
EL50 (48 hour): 3 mg/l (*Daphnia magna*, mobility)
EC50 (96 hour): 13 mg/l (*Pseudokirchnerella subcapitata*)

Long Term NOELR (28 days) 1.5 mg/l (*Fish*) QSAR
LOEC (21 days): 0.32 mg/l (*Daphnia magna*)
NOEL (96 hour) 6.3 mg/l (*Algae*)



DuPont™ Non-Stick Dry Film Lubricant with Teflon® Fluoropolymer Liquid

Persistence and degradability	Not available.
Bioaccumulative potential	Not available.
Mobility in soil	Not available.
Results of PBT and vPvB assessment	Not classified as PBT or vPvB.
Other adverse effects	None known.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods Disposal should be in accordance with local, state or national legislation. Consult an accredited waste disposal contractor or the local authority for advice.

SECTION 14: TRANSPORT INFORMATION

	Land transport (U.S. DOT)	Sea transport (IMDG)	Air transport (ICAO/IATA)
UN number	1993	1993	1993
Proper Shipping Name	Flammable liquid, n.o.s. (Isopropanol and Heptanes)	Flammable liquid, n.o.s. (Isopropanol and Heptanes)	Flammable liquid, n.o.s. (Isopropanol and Heptanes)
Transport hazard class(es)	3	3	3
Packing group	II	II	II
Environmental hazards	No.	No.	No.
Special precautions for user	None assigned	None assigned	None assigned
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: Not applicable			

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture:

TSCA (Toxic Substance Control Act) - Inventory Status: All components listed or polymer exempt.

TSCA 12(b) Export Notification: CAS 9002-84-0 Polytetrafluoroethylene

Designated Hazardous Substances and Reportable Quantities (40 CFR 302.4):

Chemical Name	CAS No.	Typical %wt.	RQ (Pounds)
None	----	----	----

SARA 311/312 - Hazard Categories:

Fire Sudden Release Reactivity Immediate (acute) Chronic (delayed)

SARA 313 - Toxic Chemicals (40 CFR 372):

Chemical Name	CAS No.	Typical %wt.
Isopropanol	67-63-0	59

SARA 302 - Extremely Hazardous Substances(40 CFR 355):

Chemical Name	CAS No.	Typical %wt.	TPQ (pounds)
None	----	----	----

California Proposition 65 List:

Chemical Name	CAS No.	Type of Toxicity
None	----	----



DuPont™ Non-Stick Dry Film Lubricant with Teflon® Fluoropolymer Liquid

SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements: 1-16.

Date of preparation: March 26, 2015

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.