



DuPont™ Silicone Lubricant with Teflon® fluoropolymer - Aerosol

SAFETY DATA SHEET

OSHA HCS (29 CFR 1910.1200)

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product identifier

| | |
|---------------|---|
| Chemical Name | Not applicable. |
| CAS No. | Mixture |
| Trade Name | DuPont™ Silicone Lubricant with Teflon® fluoropolymer - Aerosol |
| Product Code | None |

Relevant identified uses of the substance or mixture and uses advised against

| | |
|----------------------|-----------|
| Identified Use(s) | Lubricant |
| Uses Advised Against | None |

| | |
|------------------------|--|
| Company Identification | Finish Line Technologies, Inc. 50 Wireless Blvd. Hauppauge, NY 11788 |
|------------------------|--|

| | |
|---------------------------|--|
| Telephone | (631) 666-7300 |
| E-Mail (competent person) | SDSinfo@finishlineusa.com |

Emergency telephone number

| | |
|---------------------|---|
| Emergency Phone No. | Medical Emergency: PROSAR 24 hr: 1-800-217-5157 / 1-651-523-0304 |
|---------------------|---|

Transportation Emergency: CHEMTREC 24 hr. 1-800-424-9300 / 1 (703) 527-3887 (Collect calls accepted)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the substance or mixture

| | |
|-----------------------------|--|
| OSHA HCS (29 CFR 1910.1200) | Flam. Aerosol 1; Skin Irrit. 2; STOT SE 3; Asp. Tox. 1 |
|-----------------------------|--|

Label elements

Hazard Symbol



DANGER

Hazard Statement(s)

Extremely flammable aerosol.
Pressurized container: May burst if heated.
May be fatal if swallowed and enters airways.
Causes skin irritation.
May cause drowsiness or dizziness.

Precautionary Statement(s)

Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
Do not spray on an open flame or other ignition source.
Pressurized container: Do not pierce or burn, even after use.
Protect from sunlight and do not expose to temperatures exceeding 50 °C/122 °F.
Avoid breathing spray.
Wash hands and exposed skin thoroughly after handling:
IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.
Use only outdoors or in a well-ventilated area.



DuPont™ Silicone Lubricant with Teflon® fluoropolymer - Aerosol

Keep out of reach of children.

Other hazards

None

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

| Hazardous Ingredient(s) | % wt. | CAS No. |
|---|---------|-------------|
| Heptane, branched, cyclic and linear | 15 - 25 | 426260-76-6 |
| Distillates (petroleum), hydrotreated light | 15 - 25 | 64742-47-8 |
| Distillates (petroleum), blend of various solvent-refined and hydrotreated heavy paraffinic and residual oils | 1 - 20 | mixture |
| Propane | 5 - 15 | 74-98-6 |
| Butane | 5 - 15 | 106-97-8 |

Additional Information - None

SECTION 4: FIRST AID MEASURES



Description of first aid measures

Inhalation

Move person to fresh air. If breathing is labored, administer oxygen. If symptoms develop, obtain medical attention.

Skin Contact

Wash affected skin with soap and water. If symptoms develop, obtain medical attention.

Eye Contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If symptoms occur obtain medical attention.

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. Do not give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and delayed

May be fatal if swallowed and enters airways. Will cause skin irritation. Vapours may cause drowsiness and dizziness.

Indication of any immediate medical attention and special treatment needed

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

-Suitable Extinguishing Media

Extinguish with carbon dioxide, dry chemical, foam or water spray.

-Unsuitable Extinguishing Media

Do not use water jet.



DuPont™ Silicone Lubricant with Teflon® fluoropolymer - Aerosol

Special hazards arising from the substance or mixture

Highly flammable vapor (flash point below 23°C).

Advice for fire-fighters

A self contained breathing apparatus and suitable protective clothing should be worn in fire conditions. Keep containers cool by spraying with water if exposed to fire.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Take precautionary measures against static discharges. Avoid contact with skin and eyes.

Environmental precautions

Prevent liquid entering sewers, basements and workpits.

Methods and material for containment and cleaning up

Cover spills with inert absorbent material. Transfer to a container for disposal or recovery.

**Reference to other sections
Additional Information**

None
None

SECTION 7: HANDLING AND STORAGE

Precautions for safe handling

Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Avoid contact with skin and eyes. Use product in a well-ventilated area only.

Conditions for safe storage, including any incompatibilities

-Storage temperature

Keep in a cool, well ventilated place.

-Incompatible materials

This product should be stored away from sources of strong heat or oxidising chemicals.

Specific end use(s)

Lubricant

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

| SUBSTANCE. | CAS No. | (8hr TWA) | | STEL | | Note: |
|--------------------------------------|-------------|---------------------|------------------------------------|------------|-------------|--------------------------|
| | | PEL (OSHA) | TLV (ACGIH) | PEL (OSHA) | TLV (ACGIH) | |
| Heptane, branched, cyclic and linear | 426260-76-6 | 500 ppm* | 1500 mg/m ³ | ----- | ----- | *n-heptane |
| Oil mist (mineral) | ----- | 5 mg/m ³ | 5 mg/m ³ ⁽¹⁾ | ----- | ----- | ⁽¹⁾ Inhalable |
| Propane | 74-98-6 | 1000 ppm | Aspyx.# | ----- | ----- | # |

*Assure minimum oxygen content of work atmosphere.

Recommended monitoring method

NIOSH 1500 (hydrocarbons, B.P. 36 - 216 °C) ; NIOSH 5026 (Oil mist; mineral)

Exposure controls

Appropriate engineering controls

Provide adequate ventilation to ensure that the occupational exposure limit is not exceeded.

Personal protection equipment

Eye/face protection

Wear protective eyewear (goggles, face shield, or safety glasses).





DuPont™ Silicone Lubricant with Teflon® fluoropolymer - Aerosol

Skin protection (Hand protection/ Other)

Wear suitable gloves if prolonged skin contact is likely (Nitrile rubber)



Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment.



Thermal hazards

Not normally required.

Environmental Exposure Controls

None known

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

| | |
|--|------------------------------------|
| Appearance | Liquid / Liquefied gas |
| Color. | Clear / Colourless |
| Odor | Petroleum spirit |
| Odor Threshold (ppm) | Not available |
| pH (Value) | Not available |
| Melting Point (°C) / Freezing Point (°C) | Not available |
| Boiling point/boiling range (°C): | 94 - 98 (201 - 208 °F) |
| Flash Point (°C) | -104 (Propane) |
| Evaporation Rate | Not available |
| Flammability (solid, gas) | Extremely flammable |
| Explosive Limit Ranges | 2.1% - 9.5% v/v (Propane) |
| Vapour pressure (Pascal) | ca. 95 x 10 ⁴ (Propane) |
| Vapour Density (Air=1) | ca. 1.56 @ 0°C (Propane) |
| Density (g/ml) | Not available |
| Solubility (Water) | Not available |
| Solubility (Other) | Not available |
| Partition Coefficient (n-Octanol/water) | Not available |
| Auto Ignition Point (°C) | Not available |
| Decomposition Temperature (°C) | Not available |
| Kinematic Viscosity (cSt) | <10 @ 40 °C |
| Explosive properties | Not explosive. |
| Oxidizing properties | Not oxidizing. |

Other information

VOC content = 59% by wt.

SECTION 10: STABILITY AND REACTIVITY

| | |
|---|---|
| Reactivity | Stable under normal conditions. |
| Chemical stability | Stable. |
| Possibility of hazardous reactions | None anticipated. |
| Conditions to avoid | Avoid contact with heat and ignition sources. |
| Incompatible materials | Strong oxidising agents |
| Hazardous decomposition product(s) | Carbon monoxide, Carbon dioxide, Acrid smoke, Other |

SECTION 11: TOXICOLOGICAL INFORMATION

Exposure routes: Inhalation, Skin Contact, Eye Contact



DuPont™ Silicone Lubricant with Teflon® fluoropolymer - Aerosol

Acute toxicity

Oral: LD50 >5 g/kg-bw
 Dermal: LD50 >2 g/kg-bw
 Inhalation: LC50 = 65 - 103 mg/L (Vapor), 4-hr. rat
 May cause drowsiness or dizziness.
 May be fatal if swallowed and enters airways.

Irritation/Corrosivity

Causes skin irritation. Repeated exposure may cause skin dryness or cracking. Causes eye irritation.

Sensitization

It is not a skin sensitizer.

Repeated dose toxicity

NOAEC: 12350 mg/m3 (2 yr, inhal., rat, Systemic effects)
 LOAEC: 1650 mg/m3 (2 hr, inhal., rat, CNS effects)
 May cause drowsiness or dizziness.

Carcinogenicity

No data. It is unlikely to present a carcinogenic hazard to man.

| NTP | IARC | ACGIH | OSHA | NIOSH |
|-----|------|-------|------|-------|
| No. | No. | No. | No. | No. |

Mutagenicity

There is no evidence of mutagenic potential.

Toxicity for reproduction

No information available

SECTION 12: ECOLOGICAL INFORMATION

Toxicity - Substances in preparations / mixtures

Heptane, branched, cyclic and linear (CAS# 426260-76-6) - By analogy with similar materials:

| | |
|---|---|
| Short term | LL50 (96 hour): >13.4 mg/L (<i>Oncorhynchus mykiss</i>) EL50 (48 hour): 3 mg/l (<i>Daphnia magna</i> , mobility) EC50 (96 hour): 13 mg/l (<i>Pseudokirchnerella subcapitata</i>) |
| Long Term | NOELR (28 days) 1.5 mg/l (<i>Fish</i>) QSAR LOEC (21 days): 0.32 mg/l (<i>Daphnia magna</i>) NOEL (96 hour) 6.3 mg/l (<i>Algae</i>) |
| Persistence and degradability | Not available. |
| Bioaccumulative potential | Not available. |
| Mobility in soil | Not available. |
| Results of PBT and vPvB assessment | Not classified as PBT or vPvB. |
| Other adverse effects | None known. |

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal should be in accordance with local, state or national legislation. Consult an accredited waste disposal contractor or the local authority for advice.

SECTION 14: TRANSPORT INFORMATION

| | Land transport (U.S. DOT) | Sea transport (IMDG) | Air transport (ICAO/IATA) |
|-------------------------------------|------------------------------|-------------------------|------------------------------|
| UN number | 1950 | 1950 | 1950 |
| Proper Shipping Name | Aerosols, flammable | Aerosols, flammable | Aerosols, flammable |
| Transport hazard class(es) | 2.1 | 2.1 | 2.1 |
| Packing group | Not applicable | Not applicable | Not applicable |
| Environmental hazards | No. | No. | No. |
| Special precautions for user | None assigned | None assigned | None assigned |

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: Not applicable



DuPont™ Silicone Lubricant with Teflon® fluoropolymer - Aerosol

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture:

TSCA (Toxic Substance Control Act) - Inventory Status: All components listed or polymer exempt.

Designated Hazardous Substances and Reportable Quantities (40 CFR 302.4):

| Chemical Name | CAS No. | Typical %wt. | RQ (Pounds) |
|---------------|---------|--------------|-------------|
| None | ---- | ---- | ---- |

SARA 311/312 - Hazard Categories:

Fire Sudden Release Reactivity Immediate (acute) Chronic (delayed)

SARA 313 - Toxic Chemicals (40 CFR 372):

| Chemical Name | CAS No. | Typical %wt. |
|---------------|---------|--------------|
| None | ---- | ---- |

SARA 302 - Extremely Hazardous Substances(40 CFR 355):

| Chemical Name | CAS No. | Typical %wt. | TPQ (pounds) |
|---------------|---------|--------------|--------------|
| None | ---- | ---- | ---- |

California Proposition 65 List:

| Chemical Name | CAS No. | Type of Toxicity |
|---------------|---------|------------------|
| None | ---- | ---- |

SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements: 1-16.

Date of preparation: March 17, 2015

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.