



# DuPont™ Multi-Use High Performance Lubricant

## SAFETY DATA SHEET

OSHA HCS (29 CFR 1910.1200)

### SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

#### Product identifier

Chemical Name	Not applicable.
CAS No.	Mixture
Trade Name	DuPont™ Multi-Use High Performance Lubricant
Product Code	None

#### Relevant identified uses of the substance or mixture and uses advised against

Identified Use(s)	Lubricant
Uses Advised Against	None

Company Identification	Finish Line Technologies, Inc. 50 Wireless Blvd. Hauppauge, NY 11788
------------------------	--

Telephone	(631) 666-7300
E-Mail (competent person)	<a href="mailto:SDSinfo@finishlineusa.com">SDSinfo@finishlineusa.com</a>

#### Emergency telephone number

Emergency Phone No.	<b>Medical Emergency:</b> PROSAR 24 hr: 1-800-217-5157 / 1-651-523-0304
---------------------	---

**Transportation Emergency:** CHEMTREC 24 hr. 1-800-424-9300 / 1 (703) 527-3887 (Collect calls accepted)

### SECTION 2: HAZARDS IDENTIFICATION

#### Classification of the substance or mixture

OSHA HCS (29 CFR 1910.1200)	Flam. Aerosol 2; Skin Irrit. 2; STOT SE 3; Asp. Tox. 1
-----------------------------	--

#### Label elements

Hazard Symbol



**DANGER**

Signal word(s)

Hazard Statement(s)

Flammable aerosol.  
Pressurised container: May burst if heated.  
May be fatal if swallowed and enters airways.  
Causes skin irritation. Repeated exposure may cause skin dryness or cracking.  
May cause drowsiness or dizziness.

Precautionary Statement(s)

Keep away from heat/sparks/open flames/hot surfaces. – No smoking.  
Do not spray on an open flame or other ignition source.  
Pressurised container: Do not pierce or burn, even after use.  
Protect from sunlight and do not expose to temperatures exceeding 50 °C/122 °F.  
IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.



# DuPont™ Multi-Use High Performance Lubricant

Keep out of reach of children.

Other hazards

None

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Ingredient(s)	% wt.	CAS No.
Distillates (petroleum), hydrotreated light	50 - 70	64742-47-8
Heptane, branched, cyclic and linear	5 - 10	426260-76-6
Lubricating oils (petroleum), C15-50, hydrotreated neutral oil-based	10 - 15	mixture
Carbon dioxide	1 - 5	124-38-9

Additional Information - None

## SECTION 4: FIRST AID MEASURES



### Description of first aid measures

Inhalation

Move person to fresh air. If breathing is labored, administer oxygen. If symptoms develop, obtain medical attention.

Skin Contact

Wash affected skin with soap and water. If symptoms develop, obtain medical attention.

Eye Contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical advice/attention.

Ingestion

Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. Do not give anything by mouth to an unconscious person.

### Most important symptoms and effects, both acute and delayed

May be fatal if swallowed and enters airways. Repeated exposure may cause skin dryness or cracking.

### Indication of any immediate medical attention and special treatment needed

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

## SECTION 5: FIRE-FIGHTING MEASURES

### Extinguishing Media

- Suitable Extinguishing Media
- Unsuitable Extinguishing Media

Extinguish with carbon dioxide, dry chemical, foam or water spray. Do not use water jet.

### Special hazards arising from the substance or mixture

Highly flammable vapor (flash point below 23°C).

### Advice for fire-fighters

A self contained breathing apparatus and suitable protective clothing should be worn in fire conditions. Keep containers cool by spraying with water if exposed to fire.



# DuPont™ Multi-Use High Performance Lubricant

## SECTION 6: ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures**

Eliminate all ignition sources if safe to do so. Wear protective gloves/eye protection. Avoid breathing spray.

**Environmental precautions**

Prevent liquid entering sewers, basements and workpits.

**Methods and material for containment and cleaning up**

Cover spills with inert absorbent material. Transfer to a container for disposal or recovery.

**Reference to other sections  
Additional Information**

None  
None

## SECTION 7: HANDLING AND STORAGE

**Precautions for safe handling**

Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Do not spray on an open flame or other ignition source. Avoid contact with skin and eyes. Use product in a well-ventilated area only. Avoid breathing spray.

**Conditions for safe storage, including any incompatibilities**

-Storage temperature

Keep in a cool, well ventilated place. Store at temperatures not exceeding 50°C / 122 °F.

-Incompatible materials

This product should be stored away from sources of strong heat or oxidising chemicals.

**Specific end use(s)**

Lubricant

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

**Occupational Exposure Limits**

SUBSTANCE.	CAS No.	(8hr TWA)		STEL		Note:
		PEL (OSHA)	TLV (ACGIH)	PEL (OSHA)	TLV (ACGIH)	
Heptane, branched, cyclic and linear	426260-76-6	500 ppm*	1500 mg/m <sup>3</sup>	-----	-----	*n-heptane
Oil mist (mineral)	-----	5 mg/m <sup>3</sup>	5 mg/m <sup>3</sup> <sup>(1)</sup>	-----	-----	<sup>(1)</sup> Inhalable
Carbon dioxide	124-38-9	5000 ppm	5000 ppm	-----	30000 ppm	-----

\*Assure minimum oxygen content of work atmosphere.

**Recommended monitoring method**

NIOSH 1500 (hydrocarbons, B.P. 36 - 216 °C) ; NIOSH 5026 (Oil mist; mineral)

**Exposure controls**

**Appropriate engineering controls**

Provide adequate ventilation to ensure that the occupational exposure limit is not exceeded.

**Personal protection equipment**

Eye/face protection



Wear protective eyewear (goggles, face shield, or safety glasses).

Skin protection (Hand protection/ Other)



Wear suitable gloves if prolonged skin contact is likely (Nitrile rubber)



# DuPont™ Multi-Use High Performance Lubricant

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment.



Thermal hazards

Not normally required.

Environmental Exposure Controls

None known

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

Appearance	Liquid / Aerosol
Color.	White (Translucent)
Odor	Petroleum spirit
Odor Threshold (ppm)	Not available
pH (Value)	Not available
Melting Point (°C) / Freezing Point (°C)	Not available
Boiling point/boiling range (°C):	> 35 (> 95 °F)
Flash Point (°C)	< 60 (< 140 °F)
Evaporation Rate	Not available
Flammability (solid, gas)	Flammable
Explosive Limit Ranges	Not available
Vapour pressure (Pascal)	Not available
Vapour Density (Air=1)	Not available
Density (g/ml)	Not available
Solubility (Water)	Not available
Solubility (Other)	Not available
Partition Coefficient (n-Octanol/water)	Not available
Auto Ignition Point (°C)	Not available
Decomposition Temperature (°C)	Not available
Kinematic Viscosity (cSt)	<10 @ 40 °C
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
<b>Other information</b>	Not available

## SECTION 10: STABILITY AND REACTIVITY

<b>Reactivity</b>	Stable under normal conditions.
<b>Chemical stability</b>	Stable.
<b>Possibility of hazardous reactions</b>	None anticipated.
<b>Conditions to avoid</b>	Avoid contact with heat and ignition sources.
<b>Incompatible materials</b>	Strong oxidising agents
<b>Hazardous decomposition product(s)</b>	Carbon monoxide, Carbon dioxide, Acrid smoke, Other

## SECTION 11: TOXICOLOGICAL INFORMATION

**Exposure routes:** Inhalation, Skin Contact, Eye Contact

### Information on toxicological effects - Substances in preparations / mixtures

Heptane, branched, cyclic and linear (CAS# 426260-76-6) - By analogy with similar materials:

<b>Acute toxicity</b>	Oral: LD50 >5 g/kg-bw Dermal: LD50 >2 g/kg-bw Inhalation: LC50 = 65 - 103 mg/L (Vapor), 4-hr. rat May cause drowsiness or dizziness. May be fatal if swallowed and enters airways.
-----------------------	--



# DuPont™ Multi-Use High Performance Lubricant

<b>Irritation/Corrosivity</b>	Causes skin irritation. Repeated exposure may cause skin dryness or cracking. Causes eye irritation.
<b>Sensitization</b>	It is not a skin sensitizer.
<b>Repeated dose toxicity</b>	NOAEC: 12350 mg/m3 (2 yr, inhal., rat, Systemic effects) LOAEC: 1650 mg/m3 (2 hr, inhal., rat, CNS effects) May cause drowsiness or dizziness.
<b>Carcinogenicity</b>	No data. It is unlikely to present a carcinogenic hazard to man.

NTP	IARC	ACGIH	OSHA	NIOSH
No.	No.	No.	No.	No.

<b>Mutagenicity</b>	There is no evidence of mutagenic potential.
<b>Toxicity for reproduction</b>	No information available

## SECTION 12: ECOLOGICAL INFORMATION

### Ecotoxicity - Substances in preparations / mixtures

Heptane, branched, cyclic and linear (CAS# 426260-76-6) - By analogy with similar materials:

Short term	LL50 (96 hour): >13.4 mg/L ( <i>Oncorhynchus mykiss</i> ) EL50 (48 hour): 3 mg/l ( <i>Daphnia magna</i> , mobility) EC50 (96 hour): 13 mg/l ( <i>Pseudokirchnerella subcapitata</i> )
Long Term	NOELR (28 days) 1.5 mg/l ( <i>Fish</i> ) QSAR LOEC (21 days): 0.32 mg/l ( <i>Daphnia magna</i> ) NOEL (96 hour) 6.3 mg/l ( <i>Algae</i> )

<b>Persistence and degradability</b>	Not available.
<b>Bioaccumulative potential</b>	Not available.
<b>Mobility in soil</b>	Not available.
<b>Results of PBT and vPvB assessment</b>	Not classified as PBT or vPvB.
<b>Other adverse effects</b>	None known.

## SECTION 13: DISPOSAL CONSIDERATIONS

<b>Waste treatment methods</b>	Disposal should be in accordance with local, state or national legislation. Consult an accredited waste disposal contractor or the local authority for advice.
--------------------------------	--

## SECTION 14: TRANSPORT INFORMATION

	Land transport <u>(U.S. DOT)</u>	Sea transport <u>(IMDG)</u>	Air transport <u>(ICAO/IATA)</u>
<b>UN number</b>	1950	1950	1950
<b>Proper Shipping Name</b>	Aerosols, flammable	Aerosols, flammable	Aerosols, flammable
<b>Transport hazard class(es)</b>	2.1	2.1	2.1
<b>Packing group</b>	Not applicable	Not applicable	Not applicable
<b>Environmental hazards</b>	No.	No.	No.
<b>Special precautions for user</b>	None assigned	None assigned	None assigned

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: Not applicable

## SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture:



# DuPont™ Multi-Use High Performance Lubricant

TSCA (Toxic Substance Control Act) - Inventory Status: All components listed and active, or exempt.

Designated Hazardous Substances and Reportable Quantities (40 CFR 302.4):

Chemical Name	CAS No.	Typical %wt.	RQ (Pounds)
None	----	----	----

SARA 311/312 - Hazard Categories: Refer to SECTION 2 – HAZARDS IDENTIFICATION

SARA 313 - Toxic Chemicals (40 CFR 372):

Chemical Name	CAS No.	Typical %wt.
None	----	----

SARA 302 - Extremely Hazardous Substances(40 CFR 355):

Chemical Name	CAS No.	Typical %wt.	TPQ (pounds)
None	----	----	----

California Proposition 65 List:

Chemical Name	CAS No.	Type of Toxicity
None	----	----

## SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements: 1-16.

Date of preparation: January 28, 2021

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.